

# OR-T R19

## TECHNICAL DATA SHEET

Battery Powered Tool for Steel Strapping



### FEATURES

#### ■ Mobility

Free movement throughout the plant, not "chained" to an airhose

#### ■ Flexibility

Usable in both stationary and offline applications anywhere in the plant

#### ■ Functionality

No tripping over airhoses, electronically controlled strapping process guarantees accurate reproduction of tension/sealing settings

#### ■ Reliability

Accurate and reproducible strap tensioning and sealing, Swiss Made Quality, Certified by DEKRA

Strapping tool		OR-T R19
Operation mode		auto / semi / manual
Tension force range		400 – 3000 N
Tension speed		135 mm/s
Weight (incl. battery)		4.5 kg
Dimension (L x W x H)		390 x 150 x 140 mm
Working temperature		-10°C to +40°C
Relative humidity		up to 90%
Sealing type		single notch
Battery / charger		
Charger type		Bosch
Battery charger voltage		100 or 110 or 230 V
Charging time		30 min (80%) - 50 min
Battery type (standard)		Bosch Li-Ion ProCORE 18V, 4.0Ah
Cycles per battery charge		ca. 500
Strap width		13, 16, 19 mm
Strap Standard quality		
Strap thickness, mm (inch)		0,40 - 0,63 (.015" - 0.24")
Strap tensile strength, up to approx. N/mm <sup>2</sup> (lbs/sq. inch)		850 (120 000)
Strap High tensile quality		
Strap thickness, mm (inch)		0,40 - 0,63 (.015" - 0.24")
Strap tensile strength, up to approx. N/mm <sup>2</sup> (lbs/sq. inch)		1100 (157 000)
Matching seals		13, 16, 19 mm (1/2", 5/8", 3/4")

OPTIONS



- **User interface cover**  
for additional protection in harshest environment



- **Suspension bow**  
for stationary applications

